




PRODOOR
SYSTEMS

**SECTIONAL POLYSTYRENE INSULATED
COMMERCIAL DOORS
4421C | 4422C**



Your Trusted Partner for Premium Garage Door Solutions



www.prodoorsystems.com

SECTION DETAILS

4421C | 4422C

Insulated 3-layer Sandwich

10.25
R-VALUE



- Tongue and groove section joints
- Aluminum bottom seal retainer
- Galvanized steel end caps

4421 | V-Groove



4422 | Flush



FACE SHEET PROFILE

FACE SHEET THICKNESS 24 Gauge | .022

SECTION THICKNESS 2"


MAX OPENING WIDTH 24'-2"

MAX OPENING HEIGHT 16'
above 16' call your CSR


FINISH Two coat, baked-on paint system on exterior side, primer and polyester finish coat.




GLAZING OPTIONS *clear glass is standard, special order glass available upon request



24"x 8"



24"x 12"



Fullview

SECTION SCHEDULE

Door Opening Width	Max Windows
5'-0" to 9'-2"	2
9'-3" to 12'-2"	3
12'-3" to 16'-2"	4
16'-3" to 20'-2"	5
20'-3" to 24'-2"	6

Door Opening Height	Sections High
7' to 8'	4
8'-9" to 10'	5
10'-6" to 12'	6
12'-3" to 14'	7
14'-3" to 16'	8

Above 16' call your local CSR

