



PRODOOR
SYSTEMS

**SECTIONAL RIBBED STEEL COMMERCIAL
DOORS**

4120C | 4220C | 4320C



Your Trusted Partner for Premium Garage Door Solutions



www.prodoorsystems.com

SECTION DETAILS

4120C



Non-Insulated

4220C



Insulated 2-layer Vinyl Back

6.8
R-VALUE

4320C



Insulated 3-layer Steel Back

6.8
R-VALUE

FACE SHEET PROFILE Ribbed


FACE SHEET THICKNESS 24 Gauge | .022

SECTION THICKNESS 2"

MAX OPENING WIDTH **4120/4220** | 28'-2" **4320** | 24'-2"

MAX OPENING HEIGHT 18'
above 18' call your CSR


FINISH Two coat, baked-on paint system on exterior side, primer and polyester finish coat.




White



Sand




Brown




Black

GLAZING OPTIONS


*clear glass is standard, special order glass available upon request



24"x 6"



25"x 12"



Fullview

SECTION SCHEDULE

Door Opening Width	Max Windows
5'-0" to 9'-2"	2
9'-3" to 12'-2"	3
12'-3" to 16'-2"	4
16'-3" to 20'-2"	5
20'-3" to 24'-2"	6
24'-3" to 28'-2"	7

Door Opening Height	Sections High
7' to 8'	4
8'-9" to 10'	5
10'-6" to 12'	6
12'-3" to 14'	7
14'-3" to 16'	8
16'-3" to 18'	9

Above 18' call your local CSR

PROUD PARTNER OF:

